DOCUMENT RESUME

ED 197 987

SE 034 162

AUTHOR

Gales, Larry

TITLE

Programmer's Guide for Subroutine PLOT3D. Physical Processes in Terrestrial and Aquatic Ecosystems, Computer Programs and Graphics Capabilities.

Washington Univ., Seattle. Center for Quantitative

Science in Forestry, Fisheries and Wildlife. National Science Foundation, Washington, D.C.

SPONS AGENCY PUB DATE

INSTITUTION

May 78

GRANT NOTE

NSF-GZ-2980; NSF-SED74-17696 33p.: For related documents, see SE 034 160-167 and SE 033 581-597. Contains light and broken type in

domputer print-outs.

EDRS PRICE DESCRIPTORS MF01/PC02 Plus Postage.

Biological Sciences: *College Science: Computer Assisted Instruction: *Computer Graphics: *Computer Programs: Display Systems: Ecology: Higher Education:

Interdisciplinary Approach: Mathematical Applications: Physics: *Programing: Science

Education

ABSTRACT

This module is part of a series designed to be used by life science students for instruction in the application of physical theory to ecosystem operation. Most modules contain computer programs which are built around a particular application of a physical process. PLOT3D is a subroutine package which generates a variety of three-dimensional hidden line Cal Comp-type displays. The package features multiple plots per page, with or without annotation, or annotation without plots: multiple pages: automatic scaling; flexible tilting: two-dimensional interpolation over the image space: choice of size and location of plots on a page; choice of viewing angle and viewing distance: and various options which affect the appearance of the plot. PLOT3D communicates with the calling program through the following: (1) an argument list: (2) common blocks: (3) files: and (4) a set of file manipulation subroutines. An annotated listing illustrates the control, program, and input data cards for a sample run, along with the associated output. (Author/CS)

****************** Reproductions supplied by EDRS are the best that can be made from the original document.





PHYSICAL PROCESSES IN TERRESTRIAL AND AQUATIC ECOSYSTEMS COMPUTER PROGRAMS AND GRAPHICS CAPABILITIES

PROGRAMMER'S GUIDE FOR SUBROUTINE PLOT3D

of the day of the first state of the second of the second

Pathicia Dabb

to the product the Hermites eminimized to the Hermites

by

Larry Gales

CENTER FOR QUANTITATIVE SCIENCE IN
FORESTRY, FISHERIES AND WILDLIFE
University of Washington

PROGRAMMER'S GUIDE FOR SUBROUTINE PLOT3D

bу

...

Larry Gales

This instructional module is part of a series on Physical Processes in Terrestrial and Aquatic Ecosystems supported by National Science Foundation Training Grant No. GZ-2980

MAY 1978



IAN 1 9 1981

PROGRAMMER'S GUIDE FOR SUBROUTINE PLOT3D

Identification

PLOT3D -A Subroutine Which Generates Three-Dimensional Hidden Line Displays

Author -Larry Gales

Date -May, 1978- Center for Quantitative Science in Forestry, Fisheries

and Wildlife, University of Washington, Seattle, Washington 98195

Purpose

PLOT3D is a subroutine package which generates a variety of three-dimensional hidden line CalComp-tyre displays. The package features multiple plots per page, with or without annotation, or annotation without plots; multiple pages; automatic scaling; flexible titling; two-dimensional interpolation over the image space; choice of size and location of plots on a page; choice of viewing angle and viewing distance; and various options which affect the appearance of the plot. Each page of plots fits on a standard 8-1/2 x 11 inch page with margins of sufficient size to permit inclusion in three-ring binders. For a more detailed description of the purpose and usage of PLOT3D refer to its user's guide (Gales 1978).

Usage

PLOT3D communicates with the calling program through: (1) an argument list, (2) common blocks, (3) files, and (4) a set of file manipulation subroutines.



•Argument List:

PLOT3D is invoked by the following statement in the calling program:

CALL QQPL3D(TLF, ERF, DTF, DTF1, NX, NY,

- LBOX, LHIDE, XMIN, XMAX, YMIN, YMAX,
- ZMIN, ZMAX, XRICH, YRICH, DFAULT,
- XVIEW, YVIEW, ZVIEW, XC, YC,
- XSIZE, YSIZE, PAGE, TITLE, LOCTIT,
- PXC, PYC, ERR)

where QQPL3D is the main entry point in PLOT3D. All of the arguments, except PXC, PYC, and ERR are input arguments only and are unaffected by the operation of the program. ERR is an output argument which is set greater than zero if, and only if, PLOT3D detects an error. PXC and PYC are input/output arguments and contain the location of the lower left corner of the previous plot upon exit from PLOT3D. PXC and PYC should never be assigned values in the calling program except prior to the very first call, in which case they should be set to zeroes. The types, restrictions, and descriptions of the arguments are as follows:

ARGUMENT LIST

RESTRICT-

		RESTRICT-	
NAME	TYPE	IONS	DESCRIPTION
TLF	Integer	See file descriptions	The unit number of a file written by the calling program which contains titles which annotate the plot.
ERF	Integer	See file descriptions	The unit number of a file written by PLOT3D which displays error messages.
DTF	Integer	See file descriptions.	The unit number of a binary file written by the calling program which contains the X, Y and Z coordinates of the image points to be plotted.
DTF1	Integer	See file descriptions	The unit number of a binary scratch file written by PLOT3D which contains the coordinates of points to be plotted.
NX NY	Integer	$ \begin{array}{c c} 2 & \leq NX & \leq 30 \\ 2 & \leq NY & \leq 30 \end{array} $	The number of grid cells in the image space along the x and y axes.
LBOX	Integer	0, 1, 2, or 3	The box control for subroutine PICTURE. This parameter controls the structure of the three-dimensional window, or box, which contains the plot. The options are:
	·		LBOX = 0: No box lines. LBOX = 1: Surface and box lines. LBOX = 2: Surface, box, and side bars. LBOX = 3: Surface, box, side bars and labels.
			Normally, LBOX = 3.
LHIDE	Integer	0, 1, 2, -1, -2	The hidden line control parameter for subroutine PICTURE. The options are: LHIDE = 0: No hidden lines removed.
. •			<pre>LHIDE = 1: Hidden lines of plot but</pre>
		6	LHIDE < 0: Visible portions of the underside are also plotte Normally, LHIDE = 2.

			<i>→</i> 1
		RESTRICT-	
NAME	TYPE	IONS	DESCRIPTION
XMIN XMAX YMIN YMAX ZMIN ZMAX	Real	10NS ≥ -10 ²⁹ ≤ 10 ²⁹	XMIN, XMAX, YMIN, YMAX, ZMIN, and ZMAX define a three-dimensional window which encloses all the data in the image space to be displayed. Data outside the window are not shown. If one or more of the following conditions hold: XMIN > XMAX, YMIN > YMAX, ZMIN > ZMAX the computer considers the limits to
			be unspecified by the user and computes new limits for the axis or axes in question which are sufficient to include all the data along that axis or axes in the image space.
XRICH YRICH	Real	<u>></u> 0	XRICH and YRICH are the Δx and Δy increments used in two-dimensional interpolation (enrichment). If either is zero, no enrichment takes place. The user should note that the values of XRICH and YRICH should be coordinated not only with the data, but also with the size of the window set by XMIN, XMAX, YMIN, and YMAX. If either is too small, the computer will consume too much computer time, whereas large values of XRICH or YRICH will affect the appearance of the plot. Note that interpolation should only be applied to data which are correctly organized on the binary data file.
DFAULT	Real	$\frac{>}{-10^{29}}$ $\leq 10^{29}$	DFAULT is the default value assigned to all cells in the image space. DFAULT is usually set to zero.
XVIEW YVIEW ZVIEW	Real	XVIEW > XSIZE YVIEW > YSIZE ZVIEW > XSIZE ZVIEW > YSIZE	The point of view in space, in inches, from which the plot is seen by the user. Normally, XVIEW and YVIEW should be negative, indicating that the observer is behind the plot so that it appears in front of him, while ZVIEW should be positive indicating that the observer is above the plot looking down. The user may have to experiment with different values for these viewpoints in order to obtain the desired view of the plot.

		RESTRICT-	
NAME	TYPE	IONS	DESCRIPTION
XC YC	Real	$0.5 \le XC \le 8 \\ 0.5 \le YC \le 10.5$	The location on a page of the lower left corner of a box which encloses the plot. The distances are in inches from the lower left corner of the page.
XSIZE YSIZE	Real	XSIZE > .1 XC + XSIZE < 8 YSIZE > .1 YC + YSIZE < 10.5	The size of a box, in inches, which is to contain the plot.
PAGE	Logical	T or F	If PAGE = T (true), then the current page is skipped and the current plot is written on the next page. If PAGE = F (false), the current plot is written on the current page.
TITLE	Logical	T or F	If TITLE = T (true), then the current plot consists of plot titles only, with no plot. If TITLE = F (false), then both plot and plot titles are written. Note that in the former case, the entire area defined by XSIZE, YSIZE is available for plot titles (or any other text), whereas in the latter case, the plot titles are either squeezed in near the top of the area defined by XSIZE, YSIZE, or just above it (see LOCTIT).
LOCTIT	Logical	T or F	If LOCTIT is T (true), then the plot titles will be contained wholly within the region defined by XC, YC, XSIZE, and YSIZE. If LOCTIT is F (false), the plot titles are placed above and outside this region.
PXC PYC	Integer	None (set by PLOT3D)	The location of the lower left corner of the previous plot (in inches). PXC, PYC are reset to zeroes whenever PAGE is true.
ERR	Integer	None (set by PLOT3D)	An output argument which is zero if PLOT3D detects no errors, or is greater than zero if it does detect errors. See the user's guide for a detailed explanation of the error codes.

Common blocks:

PLOT3D uses blank common and four labeled common blocks named /QQPL1/, /QQPL2/, /QQPL3/, and /QQXYZ/. Blank common serves as temporary storage for the image space (F), a counter for the number of points mapped to each image cell (NP), and two temporary storage arrays (TEMPX, TEMPY), and is structured as follows:

COMMON// F(30,30), NP(30,30), TEMPX(30,30), TEMPY(30,30)

REAL F, NP, TEMPX, TEMPY

Therefore, the calling program must reserve $4 \times 30 \times 30 = 3600$ (decimal) words of workspace at the start of blank common, e.g.,

COMMON// WSPACE (3600)

REAL WSPACE

Since PLOT3D uses this area for temporary storage only and does not preserve values between calls, the calling program may access and modify this region in blank common any way it chooses, except that values stored in the first 3600 words will be destroyed when PLOT3D is called.

The three common blocks /QQPL1/, /QQPL2/, and /QQPL3/ are used only for internal operations in PLOT3D and can be ignored by the calling program. Common block /QQXYZ/, however, serves a vital role in facilitating binary input and output of data points for the image space both within the calling program and PLOT3D. /QQXYZ/ is structured as follows:

COMMON /QQXYZ/ X, Y, Z, FINI, EOFT

REAL X, Y, Z, FINI

LOGICAL EOFT

where X, Y, Z are the coordinates of one data point, FINI is the value assigned to the end-of-file indicator (-99999.0), and EOFT is a logical variable which is set true iff an end-of-file is read. Any binary data file passed to PLOT3D by a calling



program should be read, written, terminated, and rewound by the special file manipulation subroutines QQRXYZ, QQWXYZ, QQWEOF, and QQREW, respectively, contained in PLOT3D. The <u>calling program</u> must explicitly set FINI = -99999.0 before any of these routines is invoked; otherwise, FINI will be undefined and the results unpredictable.

Files:

PLOT3D uses four files named TLF, ERF, DTF, and DTF1. TLF is the unit number of a formatted file which passes plot title information to PLOT3D. It must contain four card images, each of which is at least 66 characters long, which label the top of the plot. TLF is normally written by the calling program, although it may reside on an external file. It is automatically rewound by PLOT3D at the start and end of execution.

ERF is the unit number of a formatted file written by PLOT3D which displays any error messages.

DTF is the unit number of a binary file which passes the x, y, z coordinates of plot image data points to PLOT3D. DTF is normally written by the calling program using subroutine QQWXYZ and must be terminated by an end-of-file written by QQWEOF. The order of points on DTF depends on whether enrichment (interpolation) is selected. If no enrichment is called for, the points may be ordered randomly. If two-dimensional enrichment is called for, then the points must form a sequence of triangles. For a more complete description of enrichment and its effects on ordering, refer to the user's guide. DTF is automatically rewound by PLOT3D at the start and end of execution.



DTF1 is the unit number of a binary scratch file which is written and read by PLOT3D if enrichment is selected. DTF1 is automatically rewound by PLOT3D at the start and end of execution.

The characteristics of the files used by PLOT3D are summarized as follows:

FILE A	AUTOMATIC REWIND	READ BY PLOT3D	WRITTEN BY PLOT3D	UNIQUE UNIT
TLF	Yes	Yes	No	Yes
ERF	No	No	Yes	Yes .
DTF	Yes	Yes	No	Yes
DTF1	Yes	Yes	Yes	Yes

The column labeled "AUTOMATIC REWIND" means that subroutine PLOT3D rewinds the file at the start of its execution and then rewinds it again just before it returns to the calling program. The column labeled "UNIQUE UNIT NUMBER" specifies whether or not different file names may reference the same unit number. Here, all files must be unique.

Subroutine PLOT3D does not check the files for format errors nor does it check to see if file names reference valid unit numbers. These types of errors will generally trigger error messages and actions which are peculiar to a given computer installation.

File Manipulation Subroutines:

PLOT3D contains four subroutines which manipulate the binary data files. These routines are invoked by PLOT3D and also by the calling program which prepares data for PLOT3D, and are always used in conjunction with the common block /QQXYZ/ which holds the x, y, z coordinates for a single point to be written or read. The



routines are:

QQRXYZ (FILE): Reads the x, y, z coordinates of one data point from FILE and stores the coordinates in /QQXYZ/.

QQWXYZ (FILE): Retrieves the x, y, z coordinates of a point stored in /QQXYZ/ and writes them on FILE.

QQWEOF (FILE): Writes the point (FINI, FINI, FINI) on FILE to indicate the end-of-file.

QQREW (FILE): Rewinds FILE.

As an example of the use of these routines in the calling program, consider the following fragment of computer code which writes 1000 data points on unit 1, terminates unit 1 with an end-of-file, and then reads the points back in. Note FINI must be established before the routines are called and EOFT must be cleared before testing for an end-of-file. Also note that X = Y = Z = FINI = -999999.0 in common block /QQXYZ/ when the end-of-file is read. The code is as follows:

COMMON /QQXYZ/ X, Y, Z, FINI, EOFT

C---- SET-END-OF FILE INDICATOR
FINI = -99999.0

C
C---- REWIND TAPE 1
CALL QQREW(1)

C
C---- WRITE 1000 DATA POINTS ONTO TAPE 1
DO 10 I = 1, 1000
X = •••
Y = •••
Z = •••
CALL QQWXYZ(1)
10 CONTINUE

C---- END FILE TAPE 1 CALL QQWEOF(1



```
C
C---- REWIND TAPE 1, AND PRESET EOFT TO FALSE

CALL QQREW(1 )

EOFT = .FALSE.

C
C---- READ BACK THE 1000 FOINTS

DO 20 I = 1, 2000

CALL QQRXYZ(1 )

IF (EOFT) GOTO 30

... = X

... = Y

... = Z

20 CONTINUE


C

30 CONTINUE
```



Structure

The overall structure of PLOT3D is displayed in the following flow chart:





Subroutines

The following is a list and brief description of all subroutines contained in PLOT3D in alphabetical order:

QQ2D:

Called when two-dimensional interpolation (enwichment) is selected. It transfers all points from file DTF to DTF1 and, after every third point, it calls QQTRI which adds large numbers of interpolated points to DTF1. QQ2D assumes that three consecutive points on DTF are the vertex points of a single triangle.

QQCK:

Checks the input parameters NX, NY, XSIZE, YSIZE, XC, and YC for errors in value.

QQCSIZ:

Calculates the size of characters and the distance between text lines, for the four title lines, so as to insure that they will properly fit in the space allocated within, or above, the plot.

QQER:

Writes out error messages on file ERF and sets ERR to an appropriate nonzero value.

QQF:

Reads data from a file and maps each data point within the x and y axes of the current window onto a cell in the image space F. It also accumulates the number of points mapped to each image cell, in the array NP, and tallies the number of z values which lie outside the ZMIN to ZMAX limits.

QQNCHR:

Calculates the maximum number of characters in the title lines, minus all trailing blanks.

QQPAK:

Packs text consisting of one character per word into 10 characters per word (for the CDC 6400 computer).

QQPLOT: Calls subroutine PICTURE which generates the actual CalComp plotter

commands to produce a three-dimensional hidden line plot.

QQPLT2: Calls the CalComp subroutine PLOT to initialize the plotter so that

the origin is set at a specified point.

QOPTTL: Calls QQNCHR, QQCSIZ, and QQPAK to prepare the plot titles for

plotting.

QQPTXT: Plots the titles prepared by QQPTTL by calling the CalComp plotter

routine SYMBOL which generates the plotting instructions.

QQREW: Rewinds a file.

QQRXYZ: Reads one x,y,z coordinate triple from the binary data file and stores

it in common block /QQXYZ/. If X = Y = Z = FINI, it sets EOFT =

.TRUE.

QQTRI: Accepts the x, y, z coordinates of three vertex points of a

triangular region and generates a series of equispaced linearly

interpolated points along the plane defined by the three points.

The points are written on DTF1.

QQWEOF: Writes the point (FINI, FINI, FINI) on a file. This point

establishes the end-of-file.

QQWIND: Computes the x, y, and z coordinates of a cubical window which

encloses the data. It is called if:

XMIN \geq YMAX, or

YMIN > YMAX, or

 $ZMIN \ge ZMAX.$

If any one or more of the above conditions is encountered it

computes new values for the x, y, or z axes which completely

contain the data.

QQWXYZ: Writes the x, y, z coordinates for the point currently stored in

/QQXYZ/ on a file.

External Subroutines

The following is a list and brief description of all subroutines called by PLOT3D which are not contained in the source deck.

PICTURE:

This is a very large and complex plotting routine, adapted from the program developed by Melvin L. Prueitt of Los Alamos Scientific Laboratory, which generates commands for the CalComp plotter to produce three-dimensional hidden line displays. This routine is non-ANSI and rather machine dependent.

PLOT:

This is a CalComp plotter routine which is used to set the origin of a plot.

PUTC:

This is a small machine-dependent subroutine which packs one character-per-word text arrays into n characters-per-word, where n is the maximum number of characters which can be stored in a computer word (n equals 10 on the CDC 6400).

SYMBOL:

This is a CalComp plotter command which is used to plot characters.

Coding Information *

• Literals and constants:

The literals used in PLOT3D can be divided into seven classes:

- 1) the integers 0, 1, 2 and the real numbers 0.0 and 1.0 used as initial values or offsets;
- 2) the integer 1 and the real number 1.0 used as an increment/decrement;
- 3) the integers 0, 1, 2, and 3 and the real number 0.0 used in arithmetic tests;
- 4) the integers 1, 2, and 3 used as subscripts;



- 5) the integer -3 and real number 0.0 used as arguments;
- 6) the logical constants .TRUE. and .FALSE.;
- 7) the integers 1 through 13 used as error numbers.

All constants are assigned values in the "CONSTANTS" section of each routine and are described in the following table:

CONSTANTS

NAME	VALUE	SUB	ВLОСК	DESCRIPTION
NXD	30	QQPL3D	/QQPL2/	Maximum dimension of the image space along the x axis
NYD	30	QQPL3D	/QQPL2/	Maximum dimension of the image space along the y axis
PAGEW	8.5	QQPL3D	/QQPL2/	Width of a plotter page, in inches
EXTRME	10 ³⁰	QQPL3D	/QQPL2/	An extremely large value
EPS	10 ⁻³⁰	QQPL3D	/QQPL2/	An extremely small value
MINXS	0.1	ооск		Minimum allowed value of XSIZE
MAXXC S	8.001	ооск		Maximum allowed value of XC + XSIZE
MINYS	0.1	QQCK .		Minimum allowed value of YSIZE
MAXYCS	10.501	QQCK		Maximum allowed value of YC + YSIZE
MINXC	0.499	ооск		Minimum allowed value of XC
MAXXC	8.001	ооск		Maximum allowed value of XC
MINYC	0.499	боск		Minimum allowed value of YC
MAXYC	10.501	QQCK		Maximum allowed value of YC
STDCSZ	0.27	qqcsiz	,	Size of characters, in inches, in the titles for a standard size plot
STDDY1	0.36	QQCSIZ		Vertical distance, in inches, between title lines for a standard size plot



NAME	VALUE	SUB.	BLOCK	DESCRIPTION
STDDY2	1.4	QQCSIZ		Vertical distance, in inches, between title lines on a standard size plot when titles only are plotted, without the plot itself
STDSZ	6.0	QQCSIZ		The size, in inches, of a standard size plot along the x and y axes
ROUND	1.5	QQF		A rounding factor used when locating the grid cell into which an x , y , z point is stored
BLANK	1H	QQNCHR	·	The blank character
LINE	0	QQPLOT		A parameter used by subroutine PICTURE
SC	1.0	QQPLOT		A parameter used by subroutine PICTURE
STDSZ	6.0	QQPLOT		The size, in inches, of a standard size plot
TITSZ	4.2	QQPLOT		The size, in inches, of a standard size plot when titles only are plotted
XCDSPL	0.9	QQPLOT		The standard size of XC when titles only are to be plotted
YC1	0.0	QQPLOT		The YC displacement when titles only are to be plotted
NCL	66	QQPTTL		The maximum number of characters in a title line
NLINE	4	QQPTTL		The maximum number of title lines

• Word Lengths:

All values in PLOT3D are assumed to be stored in full length single precision words. All alphanumeric values are stored one character per word, except text strings packed by QQPAK, which are stored 10 characters per word.



• Naming Conventions:

All subroutines and common blocks start with the letters "QQ" in order to insure uniqueness. In addition, all variables in a common block which are not used in a given subroutine are represented by dummy variables of the form ZZnn or ZZZn where n is a digit. These dummy variables may span more than one array or set of names. For example, assume subroutine SB1 only makes use of the variable FINI in /QQXYZ/. Then /QQXYZ/ is declared in SB1 as follows:

-

SUBROUTINE SB1

COMMON /QQXYZ/ ZZZ1(3), FINI, ZZZ2

REAL ZZZ1, FINI

LOGICAL ZZZ2

Limitations

PLOT3D checks for 11 error conditions. If any of these conditions occurs, it outputs an appropriate error message and returns to the calling program. For a description of the error conditions and messages refer to the user's guide.

PLOT3D does not check to see if the files are correctly formatted or if unit numbers are valid. Such errors are left to the computer system.

Extensions

PLOT3D can be expensive to run if large numbers of data points are to be read, generated, or displayed. Much of the execution time is consumed in the input and output of data points using binary read/write operations (formatted read/write operations are even slower). If sufficient computer memory is available, however, one can drastically reduce this time by storing the data points directly in memory



and accessing them through simple memory reference operations. The four file manipulation routines discussed above were written with just this possibility in mind. It is only necessary to alter these routines in an appropriate manner in order to simulate the binary read/write operations with retrieve/store operations. The latter are logically identical to the former but are an order of magnitude faster.

Computer Resources

Storage:

The object deck for PLOT3D occupies 4142 (octal) words of storage when compiled under the Minnesota Fortran compiler on the CDC 6400 computer. To this must be added the 3600 (decimal) words in blank common used for the image space, plus buffer areas needed for the four files TLF, ERF, DTF, and DTF1. On the CDC 6400, this amounts to approximately 4242 + 7020 + 4000 = 17162 (octal) words of storage, some of which may be shared by the calling program.*

Execution Time:

The execution time for PLOT3D depends primarily on the number of grid cells in the image space and the number of data points generated by two-dimensional interpolation. The following table gives the approximate execution times in CPU (central processing unit) seconds on the CDC 6400 computer as a function of grid size and number of data points:

21

^{*}Note that the CDC 6400 has up to four instructions per word. Hence, other computers may require substantially more space for the computer code.



PLOT OPTION	GRID SIZE	APPROX. NO. POINTS	CPU SECONDS	
No interpolation	30 by 30	24	4.0	
No interpolation	5 by 5	24	0.42	
2D interpolation	30 by 30	1200	6.72	
2D interpolation	5 by 5	1200	3.53	· ·

Sample Run

The annotated listing on the next few pages illustrates the control, program, and input data cards for a sample run, along with the associated output. The output consists of a set of plots and annotation on one page which show the effects of various plot options applied to a single file of x, y, z coordinates. Note that the input data cards are processed by a free form input system (Gales and Anderson 1978; Anderson and Gales 1978).



```
XPL3D, CM50000, T35, P2.
                       PLCT3D TEST
ACCOUNT, XXXXXXXXXXXXXXXXXX
COMMENT.
COMMENT。***************************
COMMENT. * THE ABOVE CARDS IDENTIFY THE JOB, SPECIFY THE MEMORY
COMMENT. * REQUIPEMENTS (50000 OCTAL), ESTIMATE THE CENTRAL PROCESSOR
COMMENT.* TIME (35 SECONDS). AND SPECIFY THE USERS ACCOUNT
COMMENT.
MNF, E=C, R=7, J.
COMMENT.
COMMENT.* THE ABOVE CARD CALLS THE MINNESOTA FORTRAN COMPILER TO
COMMENT.* COMPILE THE EXECUTION PROGRAM FOR PLOTAD
CCMMENT.***********************************
CCMMENT.
ATTACH, BPL3D, ID=BPL3D.
COMMENT.
COMMENT. * THE ABOVE CARD ATTACHES THE PLOTTING ROUTINE IN BINARY FORM
COMMENT.
ATTACH, BFF, ID=BFF.
COMMENT.
COMMENT.* THE ABOVE CAPD ATTACHES THE FREE-FORMAT INPUT ROUTINES IN
COMMENT. * BINARY FORM.
CCMMENT。********************************
COMMENT.
ATTACH, GRAFTN.
LIBRARY, GRAFTN.
COMMENT.
COMMENT.* THE ABOVE CARDS ATTACH THE LIBRARY
COMMENT.* ROUTINES FOR PL3D AND DESIGNATE THAT *
COMMENT. * FILE AS THE CURRENT LIBRARY.
COMMENT. ********************
COMMENT.
LOAD, BFF.
LOAD, BPL 30.
LOAD, LGO.
EXECUTE, XPL3D.
COMMENT.
COMMENT. THE ABOVE CARDS LOAD THE EXECUTION, INPUT AND PLOT ROUTINES.
COMMENT. * AND CAUSE CONTROL TO BE PASSED TO XPLAD FOR EXECUTION
CATALOG, TAPE99, RP=5.
COMMENT.
COMMENT.**********************
COMMENT.* THE ABOVE CARD SAVES THE PLOTTING
COMMENT. * TAPE, -TAPESS-, SO THAT THE PLOTS MAY *
COMMENT.* BE PREVIEWED BEFORE BFING SENT TO
COMMENT. * THE PLCT OUTUE.
COMMENT. *********
COMMENT.
COMMENT。**********************************
COMMENT.* THE BELOW CARDS ARE THE EXECUTION PROGRAM XPL30
COMMENT.*******************************
COMMENT.
                         23
```

```
*EOR
      PREGRAM XPL3D(INPUT, OUTPUT, TAPE1, TAPE2, TAPE3, TAPE5=INPUT,
        TAPE6=OLTPUT)
C
C-PURPOSE-----
      DEMONSTRATES THE USE OF THE PLOTTING PACKAGE PLOT3D
C
C
C-IDENTIFICATION------
C
                    AUGUST 1977
      DATE:
                    CENTER FOR QUANTITATIVE SCIENCE
C
      LCCATION:
                        IN FORESTRIES, FISHERIES, AND WILDLIFE
C
C
                    UNIVERSITY OF WASHINGTON
                    SEATTLE, WASHINGTON 98195
Ç
                    ANSI STANDARD FORTRAN
C
      LANGUAGE !
      INSTALLATION: CDC 6400/CYBER 73 UNDER SCOPE 3.4 0.5.
C
C
      PREGRAMMERS: L.GALES, M.BAILEY, J. SANISLO
C
C-GLOBAL VARIABLES----
C
                                 BLANK COMMON
                    * USED FOR STORAGE OF INPUT VARIABLES READ
C
C
                    * BY INPUT PACKAGE.
                    * -WSPACE- IS USED BY THE PLOT ROUTINES.
C
                    ********
C
                    WSPACE(36CC),
      COMMON / /
                                            LHIDE,
                                                    XM TN ,
                                                            * X A M X
                    NX
                            NY,
                                    LBOX,
                                                    XRICH,
                    YMIN,
                            EXANY
                                    ZMIN,
                                            ZMAX,
                                                            YRICH,
                    DEAULT, XVIEW,
                                            ZVIEW,
                                                    XC,
                                    YVIEW.
                            YSIZE,
                                    PAGE,
                                            TITLE.
                                                    LOCTIT
                    X S I Z E 🔎
      REAL
                    WSPACE
                                    LBOX,
                                            LHIDE
      INTEGER
                    NX,
                            NY,
                            XMAX.
                                    YMIN,
                                          YMAX,
                                                    ZMIN.
                                                            ZMAX,
      FEAL
                    X M I N ,
                                    DEAULT, XVIEW,
                    X-RICH.
                            YPICH,
                                                   YVIFW.
                                                            ZVTEW。
                            YC
                    XC,
                            TITLE,
                                   LCCTIT
      LOGICAL
                    PAGE
C
      DEFINITIONS
C
                    STORAGE AREA FOR PLOT POUTINES
      WSPACE(*) =
                    NUMBER OF X AND Y CELLS IN THE IMAGE SPACE
      NX \cdot NY =
C
                    BOX CONTROL FOR SUBROUTINE -PICTUPE-
      LBGX =
                    HIDDEN LINE REMOVAL FLAG FOR SUBROUTINE -PICTURE-
C
      LHIDE *
C
      XMIN, XMAX,
C
      YMIN, YMAX,
                    DEFINE A RECTANGULAR PARALLELOPIPED WHICH ENCLOSES
C
      ZMINOZMAX =
                        THE DATA TO BE PLOTIED
C
      XRICH, YRICH * THE DELTA X AND DELTA Y INCREMENTS HSED IN TWO-
C
C
                        DIMENSIONAL ENRICHMENT
C
                    THE DEFAULT VALUES ASSIGNED TO ALL POINTS
      DFAULT =
C
      XVIEW, YVIEW,
                    THE POINT OF VIEW FROM WHICH THE PLOT IS OBSERVED
C
      ZVIEW =
C
                        (IN INCHES)
                   LOCATION ON PAGE OF LOWER LEFT CORNER OF PLOT
      XC,YC =
```

ERIC

24

```
(IN INCHES)
C
       XSIZE, YSIZE = PHYSICAL SIZE OF PLOT (IN INCHES)
C
       PAGE =
                      .TRUE. IFF THE CUPRENT PLOT IS TO APPEAR ON THE NEXT
C
                          PAGE
      TITLE =
C

    TRUE. IFF THE CURRENT PLOT CONSISTS OF ONLY TEXT

C
C
                                   DATA COMMON PL301
C
                       USED FOR STORAGE OF THE DATA POINTS
C
C
       COMMON/PL3D1/ X(8),
                               Y(8),
                                       Z(8)
       REAL
                                       Z
                               Υ,
C
C
       DEFINITIONS
С
       X(*),Y(*),Z(*) = THE LOCATION OF EACH DATA POINT
C
C
C
C
С
C
                                   VERTEX COMMON PL3D2
C
                        CONTAINS THE LOCATION OF THE VERTICES
                        FOR EACH TRIANGULAR REGION
C
С
       COMMON/PL3D2/ EX(8,3), EY(8,3), EZ(8,3)
       REAL
                      EX.
C
C
      DEFINITIONS
C
C
      EX(*,*) =
                      THE X COORDINATE OF EACH VERTEX
C
                      THE Y COORDINATE OF EACH VERTEX
C
      EZ(*,*) =
                      THE Z COOPDINATE OF EACH VERTEX
C
C
C
C
C
                                       COMMON QQXYZ
C
                        USED IN QOPL3D FOR ACCESSING THE DATA
C
                        POINTS AND CHECKING FOR AN END-OF-FILE
C
C
      COMMON/QQXYZ/ ZZZ1(3), FINI,
                      ZZZZ
                      ZZZI,
                              FINI
      LOGICAL
                     Z. Z Z Z
C
C
      DEFINITIONS
C
      FINI = -
                     -99999.0, AN END-DE-FILE MARK
C
C-LOCAL VARIABLES---
      INTEGER
                     TLF
                              ERF,
                                       DTF,
                                               DTF1,
                                                        INF,
                                                                 ECF,
```

```
OCF.
                                    C(48),
                            ERR,
                                           I,
                                                   J,
      REAL
                    PXC,
                            PYC
C
C
      DEFINITIONS
C
C
      TLF *
                    TITLE FILE CONTAINING FOUR TITLES WHICH LABEL PLCT
C
      FRF =
                    THE ERROR MESSAGE FILE
C
      DTF =
                    DATA FILE OF X, Y, AND Z COORDINATES
C
      DTF1 =
                    SCRATCH DATA FILE
C
                    INPUT FILE CONTAINING VARIABLE VALUES
      INF =
C
                    FILE USED TO ECHO INPUT
      ECF =
C
                    DECLARATION FILE USED TO DECLARE INPUT VARIABLES
      DCF =
C
      ERP =
                    ERROR NUMPER
C
      C(*) =
                    THE TITLE TEXT
C
   - I 9 J 9 K =
                    LCOP INDICES
C
      PXC, PYC =
                    LOCATION OF THE LOWER LEFT CORNER OF THE PREVIOUS
                        PLOT (IN INCHES)
C
C-SURROUTINES-----
C
                    EL
C
                   NMLIST .
C
C-FXTERNALS----
C
C
      QCPL3D
                   THE PLOTTING POUTINE
C
      PLCT, PLOTS
                    THE INITIALIZATION AND TERMINATION POUTINES FOR
C
                    THE PLOTTER (LOCATED IN THE GRAPHICS LIBRARY)
      QOWFOR
                   WRITES AN END-OF-FILE MARK ON THE DESIGNATED FILE
                    (LOCATED IN THE PLOTTING PACKAGE)
                    READS INPUT VARIABLES IN FREE FORMAT
      GOREAD
C-FILES----
C
      TLF
                   INPUT, FORMATTED,
                                           TEXTFILE
                                           ERROR MESSAGE FILE
C
      ERF
                   BUTPUT, FORMATTED,
C
      DTF
                   INPUT
                           BINARY,
                                           DATA FILE OF COORDINATES
C
                   INJOUT, BINARY,
                                           SCRATCH DATA FILE
      DTF1
                           FORMATTED.
C
      INF
                   INPUT.
                                           INPUT FILE
C
                   QUT/IN, FORMATTED,
      DCF
                                           DECLAPATION FILE
                   OUTPUT, FORMATTED,
      ECF
                                           ECHO FILE
C-CONSTANTS-----
                                         3.0,
      DATA
                   X/ 1.0, 3.0,
                                   2.0,
                                              4.2.
                                                          4.5.
                                                     5.0,
                                                                3.0 /
      DATA
                   Y /
                       3.0,
                                               2.8, . 3.0,
                                                           2.5,
                             4.0,
                                   2.0,
                                         2.4,
                                                                 1 • C
      DATA
                   TLF,
                           ERF,
                                   DTF,
                                           DTF1.
                                                   INF.
                                                           F C F
                    3,
                                    1,
                                            2,
                                                    5,
                            6,
                   OCF,
                           FINI
                    1,
                          -94999.0
                   C/
                           8 * 1 H X >
                                           32*1HT
                                   8*1HY>
C
C
C-INITIALIZATIONS-----
C
C
                       /* THE CALL TO -PLOTS- INITIALIZES THE PLOTTER
                   CALL PLOTS
                                       26
```

ERIC*

```
PXC = 0.0
                      PYC = 0.0
                          /* THE CALL TO -NMLIST- DECLARES INPUT VARIABLES
C
                      CALL NMLIST (3600, 1H , DCF, ERF, ERP)
                          /# THE CALL TO -GOREAD- READS INITIAL VALUES
C
                      CALL QQREAD(INF, ECF, FRF, ERR)
C
C
                      DO 701 I=1,4
                          GOTO(10,20,30,40),I
C
   10
                          DO 702 J=1,8
                              Z(J) = 1.0
                          CONTINUE
  702
                              /* READ PLOT PARAMETERS
C
                          CALL OQREAD(INF, ECF, ERF, ERR)
                          GOTO 999
C
                          Z(2) = 9.0
   20
                          Z(4) = 9.0
                          Z(5) = 9.0
C
                              /* READ PLOT PARAMETERS.
                          CALL QUREAD(INF, ECF, ERF, ERR)
                          GOTO 999
                          DO 703 J=1,8
  3 C
                              Z(J) = 9.0
                          CONTINUE
  703
                          Z(5) = 0.0
                               /* READ PLOT PARAMETERS
C
                          CALL QQREAD(INF, ECF, ERF, ERR)
                          GOTO 999
C
C
                              /* READ PLOT PARAMETERS
                          CALL QQREAD(INF, ECF, ERF, ERR)
   40
                          GOTO, 998
C
  999
                          CALL FL(1, 1,3,2)
                          CALL EL (2, 2,3,4)
                          CALL EL (3, 2,4,5)
                          CALL EL (4, 2,5,6)
                          CALL FL(5, 5,6,7)
                          CALL EL (6, 5,8,7)
                          CALL EL (7, 5,4,8)
                          CALL EL (8, 4,3,8)
                          DO 704 J=1,8
                              DC 705 K=1,3
                                  WRITE(OTF) EX(J,K),EY(J,K),EZ(J,K)
  705
                              CCNTINUE
                          CONTINUE
  704
                          CALL GOWEDF (DTF
  998
                          WRITE(TLF,1) C
    1 FORMAT
                          (8A10)
                          CALL COPL3D(TLF, ERF, DTF, DTF1, NY, NY, LBOX, LHICE,
                                       XMIN, XMAX, YMIN, YMAX, ZMIN, 7MAX,
                                       XRICH, YRICH, DFAULT, XVTFW, YVIEW,
                              27
                                       ZVIEW, XC, YC, XSIZE, YSIZE, PAGE, TITLE,
                                       LOCTIT,
                                                 PXC,PYC, FRR)
```




```
CONTINUE
   701
C
                          /* THE CALL TO -PLOT(0,0,999)- TERMINATES THE
C
                          /* PLCTTER
C
                      CALL PLOT(0,0,999)
                      STOP
                      END
       SUBROUTINE FL(I, I1, I2, I3)
C
       CALCULATES THE VERTICES OF EACH TRIANGULAR REGION
C
C
       INTEGER I, II, I2, I3
C
       DEFINITIONS
       I, I1, I2, I3 = INDICES: FOR THE CALULATION OF THE VERTICES
C-GLOBAL VARIABLES----
       NOTE: FOR DEFINITIONS REFER TO MAIN PROGRAM
C
C
       COMMON/PL3D1/ X(8).
                              Y(8),
                                       2(9)
C
C
       COMMON/PL3D2/ EX(8,3), EY(8,3), EZ(P,3)
                      EX, EY, EZ
Ċ
                      \mathsf{EX}(\mathsf{I},\mathsf{1}) = \mathsf{X}(\mathsf{I}\mathsf{1})
                      EX(T,2) = X(T2)
                      EX(I_93) = X(I3)
                      EY(I,1) = Y(I1)
                      EY(I,2) = Y(I2)
                      EY(I,3) = Y(I3)
                      EZ(I,1) = Z(I1)
                      EZ(I,2) = Z(I2)
                      EZ(I,3) = Z(I3)
                      RETURN
       SUBROUTINE NMLIST(INDX, NAME, DCF, ERF, ERR)
· C
      WRITE DECLARATION FILE USED BY FREE-FORMAT INPUT ROUTINES
C
C
C
                                                      ERR
                              NAME,
                                       DCF,
                                               ERF,
      INTEGER
                    INDX,
```

ERIC Full text Provided by ERIC

```
C
Č
      DEFINITIONS
C
C
                     START OF VARIABLE STOPAGE IN BLANK COMMON
      INDX =
C
                     I/O LIST IDENTIFIER
      NAME =
C
                     DECLARATION FILE
      DCF
C
                     ERROR FILE
      EPF
                     ERROR FLAG (REMAINS O IF NO ERRORS)
C
      ERR
C
C
C-EXTERNALS----
                     FREE-FORMAT INPUT ROUTINE TO PROCESS VARIABLES LIST
C
      QQINTL
C
C-START----
                     REWIND DCF
                     WRITE(DCF,1)
                     REWIND DOF
                     CALL QQINTL(INDX, NAME, DCF, ERF,
                                                        ERR)
                     REWIND DCF
                     RETURN
    1 FORMAT(
                              NX.
     • £ 2H
                 INTEGER
                                       NY.
                                               LBOX.
                                                        LHIDE
                              XMIN,
     ./62H
                 REAL
                                       XMAX
                                               YMIN,
                                                        YMAY,
                                                                 7MTN.
     ./62H
                              ZMAX,
                                       XRICH,
                                               YRICH,
                                                        DEAULT, XVTEW,
                              YVIEW,
                                       ZVIEW,
                                               XC,
                                                        ٧٢,
                                                                 XSIZF,
     ./62H
                              YSIZE
     ./62H
                              PAGE,
                                       TITLE,
                                               LOCTIT
                 LOGICAL
     ./62H
     ./62H
                 $
     ./62H
                 $
     .;
                     END
*EDR
```

```
/* INITIAL PLOT PARAMETERS */
             XMAX = 5.0, YMIN = 1.0, YMAX = 4.0,
"XMIN = 1.0
             ZMAX = 15.0, XRICH = 0.05, YRICH = 0.05, DFAULT = C.0,
 ZMIN = 0.0
 XVIEW = 5.0; YVIEW = 13.228; NX = 20; NY = 20;
 ZVIEW = 30.0,
 LBOX = 3, LHIDE = 2
 /* PARAMETERS FOR PLOT 1 */
 /*
  XC = 1.5, YC = 6.0, XSIZF = 2.0, YSIZE = 2.0,
   TITLE = .F., LOCTIT = .F.
 /* PARAMETERS FOR PLOT 2 */
 / *
   XC = 5.0, LOCTIT = .T. $
 /*
 /* PARAMETERS FOR PLOT 3 */
   XC = 3.0, YC = 3.5, XSIZE = 3.0, YSIZE = 3.0, LOCTIT = .F.
 /*
/* PARAMETERS FOR PLOT 4 */
/*
   XC = 3.0, YC = 1.5, XSIZE = 5.0, YSIZE = 1.0,
   TITLE = .T.
*EDR
* E O F
```

. ...



X	X	X	X	X	X	Χ
Y	Y	Y	Y	Υ	Υ ,	Y
T	Τ	• Т	T	τ	T	r
٠ ٢	τ	T	T	T	T	r

Acknowledgments

We are indebted to Dr. Melvin L. Prueitt of the Los Alamos Scientific Laboratory for the original PICTURE program which is used in PLOT3D as a subroutine.

1

References

- Anderson, L. and L. Gales. 1978. Programmer's guide for FFORM: a format free input system. Center for Quantitative Science in Forestry, Fisheries, and Wildlife, University of Washington, Seattle, Washington.
- Gales, L. and L. Anderson. 1978. User's guide for FFORM: a format free input system. Center for Quantitative Science in Forestry, Fisheries and Wildlife, University of Washington, Seattle, Washington.
- Gales, L. 1978. User's guide for subroutine PLOT3D. Center for Quantitative Science in Forestry, Fisheries, and Wildlife, University of Washington, Seattle, Washington.